

MEMS 16X16 OPTICAL SWITCHING SYSTEM

OSS Model, Single Mode Fiber, Network Grade



DiCon’s **Optical Switching System (OSS)** is an all-optical non-blocking cross-connect switch. This rack-mount device is designed with DiCon’s proprietary 3D MEMS mirror technology and delivers industry-leading optical performance. The unit works without any position sensor or feedback loop, and the optical signals can pass through the equipment without any observable dithering artifacts. The **OSS** can switch repeatedly with great accuracy and maintain long-term connectivity with superior stability even when there is no optical signal in the fiber.

The chassis is compact, taking minimal rack space. It is also lightweight and can be picked up easily for installation. The **OSS** comes with multiple control interfaces so authorized administrators can automate network management and set user permissions in a Software Defined Network (SDN). This product can be ordered in standard simplex or duplex configurations, and customized port arrangements are available upon request. Optical power monitors and attenuators can be added to each path as options.

Key Features

- Market Leading Performance with Recognized Reliability
- Low Loss with High Stability & No Dithering Artifacts
- Compact, Lightweight, Easy to Transport
- Switches Fast & Consumes Low Power
- Operates Bi-Directionally & Works with Dark Fibers
- Supports Software Defined Networks

Applications

- Optical Network Management
- Quantum Communications
- Data Center Interconnect
- AI (Artificial Intelligence) Networks
- LLM (Large Language Models) Machine Training
- Cyber Security & Monitoring
- Network Test Automation



ORDERING INFORMATION

OSS - N - 9 - - -

Grade

N

Network

Configuration

S16x16

Simplex 16x16

SMxN

Simplex (M, N≤16)

D16

Duplex 16 Ports

D#

Duplex (#≤16)

Function

S

Matrix Switch Only

SA

VOA Only

MS

M Side Power Monitor

MSA

M Side Power Monitor & VOA

SN

N Side Power Monitor

SAN

N Side Power Monitor & VOA

MSN

Both Sides Power Monitor

MSAN

Both Sides Power Monitor & VOA

D

Matrix Switch Only

DA

VOA Only

DP

Power Monitor (B Ports / Outputs)

DAP

Power Monitor & VOA (B Ports / Outputs)

Fiber Type

9

9/125 μm SMF

Other fiber options available upon request

Test Wavelength

O

1310 nm

C

1550 nm

L

1590 nm

Use "I" to add multiple wavelengths. E.g., O/C or O/C/L

Chassis Type

1U

1U

2U

2U

3U

3U

Please consult DiCon

See "Mechanical Specifications"

Power

A1

AC 100-240V Single

D1

DC -48V Single

A2

AC 100-240V Redundant

D2

DC -48V Redundant

Bulkhead Connector Type

LC

LC/UPC

LC/APC

LC/APC

RLC

LC/UPC on Removable Panel

RLC/APC

LC/APC on Removable Panel

HLC

High Density LC/UPC

HLC/APC

High Density LC/APC

M8F

MTP-8 Female APC

M8M

MTP-8 Male APC

M12F

MTP-12 Female APC

M12M

MTP-12 Male APC

M24F

MTP-24 Female APC

M24M

MTP-24 Male APC

Other connector types are available upon request

Connector Location

F

Front

R

Rear

# MEMS 16X16 OPTICAL SWITCHING SYSTEM

## OSS Model, Single Mode Fiber, Network Grade

### OPTICAL SPECIFICATIONS<sup>1</sup>

Operating Wavelength	1260 to 1675 nm
Insertion Loss <sup>2</sup>	< 1.0 dB
Insertion Loss (with 1 OPM) <sup>2</sup>	< 1.3 dB
Insertion Loss (with 2 OPM) <sup>2</sup>	< 1.6 dB
Loss Repeatability <sup>3</sup>	+/- 0.03 dB
Connection Stability <sup>4,5</sup>	+/- 0.03 dB
PDL <sup>5</sup>	< 0.1 dB
PDL with OPM <sup>5</sup>	< 0.3 dB
WDL <sup>5,6</sup>	< 0.3 dB
Crosstalk <sup>5</sup>	< -60 dB
Data Latency <sup>5</sup>	< 20 ns
Back Reflection	< -50 dB
Optical Transition Time <sup>5,7</sup>	< 25 ms
Switch Lifetime	> 1 Billion Cycles
Input Power Range	Dark to +27 dBm
OPM Dynamic Range	-50 to +22 dBm
OPM Relative Accuracy	+/-0.2 dB @ > -30 dBm +/-0.5 dB @ > -50 dBm

1. Measured separately for each Test Wavelength
2. Measured with 3-jumper method or equivalent. See TIA/EIA 526-7.
3. Over 100 cycles
4. 1 Hz sampling rate for 15 min
5. Met by design, not measured
6. Test Wavelength +/-20nm
7. Optical transition time for all ports switching concurrently, not including command processing overhead

### ELECTRICAL SPECIFICATIONS

Power Consumption*	< 20W Steady State < 30W at Startup
Power Supply Options	Redundant Power Supply, 100-240 VAC or -48 VDC
Network Interface Card	RJ45 Dual Redundant Gigabit Ethernet
SDN & Automation Interfaces	REST API, NETCONF, SNMPv3, TL1, Web GUI, RS232

\*Power is measured with 2 OPM

### ENVIRONMENTAL SPECIFICATIONS

Operating Temperature	0 to 50°C, < 85% RH
Storage Temperature	-40 to 70°C, < 40% RH

### MECHANICAL SPECIFICATIONS

Chassis Width	483 mm (19")
Chassis Depth*	435 mm (17") 559 mm (22") 762 mm (30") 889 mm (35") 1016 mm (40")
Chassis Height	1U (with LC)

\*Please consult DiCon

